



KEY FEATURES:

- Improved initial response and higher friction through the low and intermediate temperature range
- Increased temperature range with longer wear rates
- Decreased engagement noise and lowered dust
- Consistent engagement, response, modulation, and deceleration rates during intermittent high heat cycles such as track-time events

Wilwood's popular **BP-20** compound **SmartPad** has been re-formulated to provide the highest performance dual-sport street and track pads ever offered.

These new attributes retain the street-friendly nature of the **BP-20** compound while reducing dust, noise, and rotor wear.

APPLICATIONS:

- Street & Strip
- Auto-Cross
- Dirt Tracks
- Off-Road
- Towing



BP-20 SmartPad meets the NSF Leafmark N standard as an environment-friendly compound.

NEW PART NUMBERS:

The new formula **BP-20** pads can be identified by a new part number system that quickly identifies the pad type.

ORDERING INFO: PH: 805.388.1188 • FAX: 805.388.4938 • wilwood.com • info@wilwood.com

CALIPER FITMENT	PAD TYPE	NEW PART NO.	REPLACES
Aero 4/6/DM	6617-20, .67" Thick	150-20-6617K	150-9489K
DynaPro6	6712-20, .49" Thick	150-20-6712K	150-10007K
DynaPro Single	6812-20, .50" Thick	150-20-6812K	150-9765K
Forged Dynalite	7112-20, .49" Thick	150-20-7112K	150-9413K
Superlite 4/6, Narrow	7416-20, .65" Thick	150-20-7416K	150-9415K
Superlite 4/6, Wide	7420-20, .80" Thick	150-20-7420K	150-9416K
Dynapro / UTV4/6	7812-20, .49" Thick	150-20-7812K	150-9418K
Narrow Dynalite / DynaPro	7816-20, .60" Thick	150-20-7816K	150-9419K
Powerlite	7912-20, .49" Thick	150-20-7912K	150-9420K
D154, GM Metric	D154-20, .52" Thick	150-20-D154K	150-9422K
D52, GM	D52-20, .58 & .52" Thick	150-20-D52K	150-9421K
GP200 - Coming Spring 2023	4908-20, .31" Thick	150-20-4908K	150-14981K