

# BP-45 HIGH-PERFORMANCE BRAKE PADS

Wilwood's new **BP-45** compound has been formulated to provide smooth friction throughout the temperature curve, providing drivers who compete on most circuits with consistent and accurate pedal feel during heat cycles in short and long hard-pressure brake zones. Developed for racers seeking a high-friction compound for iron and steel rotors.



- VERY HIGH FRICTION
- HIGH TORQUE CONTROL

### APPLICATIONS:

- All race vehicles

### KEY FEATURES:

- Great low temperature friction
- Smooth friction increase as rotor temperature rises
- High-friction compound for all types of racing
- Consistent pedal feel
- For use with iron or steel rotors

ORDERING INFO: PH: 805.388.1188 • [wilwood.com](http://wilwood.com) • [info@wilwood.com](mailto:info@wilwood.com)

CALIPER FITMENT	PAD TYPE	THICKNESS	PART NO. - Axle Set
Aero 4 /6 /DM	6617-45	.67"	<a href="#">150-45-6617K</a>
Aero 4 /6 /DM	6620-45	.80"	<a href="#">150-45-6620K</a>
DynaPro6	6712-45	.49"	<a href="#">150-45-6712K</a>
DynaPro Single	6812-45	.50"	<a href="#">150-45-6812K</a>
Dynalite	7112-45	.49"	<a href="#">150-45-7112K</a>
Superlite 4/6, Narrow	7416-45	.65"	<a href="#">150-45-7416K</a>
Superlite 4/6, Wide	7420-45	.80"	<a href="#">150-45-7420K</a>
Grand National	7520-45	.80"	<a href="#">150-45-7520K</a>
Dynapro / UTV4/6	7812-45	.49"	<a href="#">150-45-7812K</a>
Narrow Dynalite / DynaPro	7816-45	.60"	<a href="#">150-45-7816K</a>
Powerlite	7912-45	.49"	<a href="#">150-45-7912K</a>
D154, GM Metric	D154-45	.52"	<a href="#">150-45-D154K</a>
D52, GM (Inners, Outers)	D0052-45	.58" & .52"	<a href="#">150-45-D52K</a>
XRZ	10420-45	.80"	<a href="#">150-45-10420K</a>



1 = Moderate / 10 = Excellent

