

Big Brake Kits for Roadster Shop RSF-2 Forged Spindle

Wilwood offers owners and builders alike front big brake kits specifically engineered for the new Roadster Shop Forged Spindles, providing the fitment and high performance you demand. Kit rotor sizes range from 11.38" up to 15.00", with a compatible Wilwood engineered caliper and performance brake pads.

Whether you ordered a SPEC or REVO RS chassis, or are simply using the **RSF-2** Forged Spindles on another chassis, Wilwood has the brake kits for your application.

KITS FEATURE:

- Complete bolt-on performance upgrade using Wilwood's competition-proven calipers and modern manufacturing technologies
- Fits Roadster Shop RSF-2 Forged 6000 series spindle

CALIPERS:

SX6R / AEROLITE 6 / SUPERLITE 6 / DYNAPRO 6 / DYNALITE

- Rigid, stress-flow forged lightweight aluminum calipers start at only 3 lbs. and provide super strength against deflection under load
- Calipers offer pure-bred racing technology with a contemporary design to deliver superior braking and style
- Heavy-duty stopping power with minimal deflection provided by removable bridge bolt or rigid center bridge
- Calipers offered in gloss red or black powder coat with many other optional color choices available (additional charges apply)

ROTORS: GTB SLOTTED / SRP DRILLED & SLOTTED

- Wilwood's E-coated **GTB** slotted, and **SRP** drilled & slotted faces offer high-performance and high styling
- Up to 72 cooling vanes improve thermal capacity, enhancing performance and extending service life
- Proprietary iron alloy **Spec37** rotors were developed to withstand extreme temperatures with a high degree of resistance against distortion and cracking
- Sizes: 11.38"x.81" / 12.19"x.81" / 12.88"x1.10" / 14.00"x1.25" / 15.00"x1.25"

BRAKE PADS: BP-10

- **BP-10** street performance pads provide smooth and consistent response with long wear (other compounds available)

INSTALLATION PARTS:

- Caliper brackets and premium-grade installation hardware included. Flexline kits available separately by application

SX6R 15.00" Kit
P/N: [140-18368-DR](#)



Aerolite 14.00" Kit
P/N: [140-18367](#)



Superlite 12.88" Kit
P/N: [140-18366](#)



Dynapro6 12.19" Kit
P/N: [140-18365-DR](#)



Dynalite 11.38" Kit
P/N: [140-18364-D](#)



FDLI 11.38"
140-18364-DR



DP6 12.19"
140-18365-DR



FNSL6 12.88"
140-18366-DR



AER06 14.00"
140-18367-DR



SX6R 15.00"
140-18368-DR



140-18364-D



140-18364-R



140-18364



140-18365-D



140-18365-R



140-18365



140-18366-D



140-18366-R



140-18366



140-18367-D



140-18367-R



140-18367



140-18368-D



140-18368-R



140-18368



BRAKE KITS ORDERING INFO: PH: 805.388.1188 • FAX: 805.388.4938 • wilwood.com • info@wilwood.com

BLACK	RED	DESCRIPTION	CALIPER TYPE	ROTOR SIZE	ROTOR TYPE
140-18364	140-18364-R	Kit, Front, FDLI 4, RS Forged Spindle RSF-2	Dynalite 4	11.38" x .81"	GTB Slotted, <i>Spec37</i> , 36 Curved Vane
140-18364-D	140-18364-DR	Kit, Front, FDLI 4, RS Forged Spindle RSF-2	Dynalite 4	11.38" x .81"	SRP Drilled & Slotted, <i>Spec37</i> , 36 Curved Vane
140-18365	140-18365-R	Kit, Front, DP6, RS Forged Spindle RSF-2	Dynapro 6	12.19" x .81"	GTB Slotted, <i>Spec37</i> , 36 Curved Vane
140-18365-D	140-18365-DR	Kit, Front, DP6, RS Forged Spindle RSF-2	Dynapro 6	12.19" x .81"	SRP Drilled & Slotted, <i>Spec37</i> , 36 Curved Vane
140-18366	140-18366-R	Kit, Front, FNSL6, RS Forged Spindle RSF-2	Superlite 6	12.88" x 1.10"	GTB Slotted, <i>Spec37</i> , 48 Curved Vane
140-18366-D	140-18366-DR	Kit, Front, FNSL6, RS Forged Spindle RSF-2	Superlite 6	12.88" x 1.10"	SRP Drilled & Slotted, <i>Spec37</i> , 48 Curved Vane
140-18367	140-18367-R	Kit, Front, AER06, RS Forged Spindle RSF-2	Aerolite 6	14.00" x 1.25"	GTB Slotted, <i>Spec37</i> , 72 Curved Vane
140-18367-D	140-18367-DR	Kit, Front, AER06, RS Forged Spindle RSF-2	Aerolite 6	14.00" x 1.25"	SRP Drilled & Slotted, <i>Spec37</i> , 72 Curved Vane
140-18368	140-18368-R	Kit, Front, SX6R, RS Forged Spindle RSF-2	SX6R	15.00" x 1.25"	GTB Slotted, <i>Spec37</i> , 72 Curved Vane
140-18368-D	140-18368-DR	Kit, Front, SX6R, RS Forged Spindle RSF-2	SX6R	15.00" x 1.25"	SRP Drilled & Slotted, <i>Spec37</i> , 72 Curved Vane